



CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT
For additional copies call
800-227-6489

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Rolando A Davila

Quality Assurance Manager

1SERIES-BPS®

HEAT NO.:3114690 SECTION: ANG 2 X 2x1/4 20'0" A36/52950 GRADE: ASTM A36-19/A529-14 Gr 50 ROLL DATE: 05/13/2022 MELT DATE: 04/23/2022 Cert. No.: 85121235 / 114690A113	S Superior Supply & Steel Co O L 318 N Cities Service Hwy D Sulphur LA US 70663-5424 T 3376252300 O 3376258509	S Superior Supply & Steel H I 318 City Service Highway P Sulphur LA US 70663-0000 T 3376252300 O 3376258509	Delivery#: 85121235 BOL#: 74909612 CUST PO#: 235301-11 CUST P/N: DLVRY LBS / HEAT: 4657.000 LB DLVRY PCS / HEAT: 73 EA
--	--	---	---

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.10%	Elongation test 2	30%		
Mn	1.04%	Elongation Gage Lgth test 2	8IN		
P	0.009%				
S	0.030%				
Si	0.20%				
Cu	0.31%				
Cr	0.09%				
Ni	0.12%				
Mo	0.040%				
V	0.000%				
Cb	0.010%				
Sn	0.012%				
Al	0.005%				
Carbon Eq A529	0.36%				
Yield Strength test 1	54.1ksi				
Tensile Strength test 1	75.7ksi				
Elongation test 1	30%				
Elongation Gage Lgth test 1	8IN				
Yield Strength test 2	54.5ksi				
Tensile Strength test 2	74.6ksi				

The Following is true of the material represented by this MTR:
**Material is fully killed and is Hot Rolled Steel*
**100% melted, rolled, and manufactured in the USA*
**EN10204:2004 3.1 compliant*
**Contains no weld repair*
**Contains no Mercury contamination*
**Manufactured in accordance with the latest version of the plant quality manual*
**Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661*
**Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov*

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W