



CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT

For additional copies call
800-227-6489

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Rolando A Davila

Quality Assurance Manager

1SERIES-BPS[®]

HEAT NO.:3116796 SECTION: FLAT 1/4x4 20'0" A36/52950 GRADE: ASTM A36-19/A529-19 GR 50 ROLL DATE: 07/17/2022 MELT DATE: 07/14/2022 Cert. No.: 85147687 / 116796A934	S O L D T O		Delivery#: 85147687 BOL#: 74949108 CUST PO#: 235803-11 CUST P/N: DLVRY LBS / HEAT: 8976.000 LB DLVRY PCS / HEAT: 132 EA
---	--------------------------------	--	--

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.10%	Yield Strength test 2	55.5ksi		
Mn	1.02%	Tensile Strength test 2	76.1ksi		
P	0.015%	Elongation test 2	29%		
S	0.038%	Elongation Gage Lgth test 2	8IN		
Si	0.21%				
Cu	0.30%				
Cr	0.11%				
Ni	0.14%				
Mo	0.037%				
V	0.000%				
Cb	0.015%				
Sn	0.009%				
Al	0.001%				
Carbon Eq F1554	0.29%				
Carbon Eq A529	0.37%				
Yield Strength test 1	54.2ksi				
Tensile Strength test 1	75.9ksi				
Elongation test 1	27%				
Elongation Gage Lgth test 1	8IN				
				<p>The Following is true of the material represented by this MTR:</p> <ul style="list-style-type: none"> *Material is fully killed and is Hot Rolled Steel *100% melted, rolled, and manufactured in the USA *EN10204:2004 3.1 compliant *Contains no weld repair *Contains no Mercury contamination *Manufactured in accordance with the latest version of the plant quality manual *Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661 *Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov 	

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W