



CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT

For additional copies call
800-227-6489

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Rolando A Davila
Rolando A Davila
Quality Assurance Manager

1 SERIES-BPS

HEAT NO.: 3120882
SECTION: ANG 3 X 3x3/8 20'0" A36/52950
GRADE: ASTM A36-19/A529-14 Gr 50
ROLL DATE: 02/20/2023
MELT DATE: 01/08/2023
Cert. No.: 85357198 / 120882A898

S O L D T O
Superior Supply & Steel Co
318 N CITIES SERVICE HWY
SULPHUR LA
US 70663-5424
3376252300
3376258509

S H I P T O
Superior Supply & Steel Co
318 N CITIES SERVICE HWY
SULPHUR LA
US 70663-5424
3376252300
3376258509

Delivery#: 85357198
BOL#: 75260608
CUST PO#: P0239413
CUST P/N:
DLVRY LBS / HEAT: 9216.000 LB
DLVRY PCS / HEAT: 64 EA

Characteristic Value

Characteristic	Value
C	0.11%
Mn	0.96%
P	0.018%
S	0.042%
Si	0.20%
Cu	0.40%
Cr	0.13%
Ni	0.12%
Mo	0.038%
V	0.000%
Cb	0.013%
Sn	0.015%
Al	0.000%
Carbon Eq A529	0.37%
Carbon Eq A992	0.34%

Yield Strength test 1	55.0ksi
Tensile Strength test 1	76.4ksi
Elongation test 1	33%
Elongation Gage Lgth test 1	8IN

Characteristic Value

Yield to tensile ratio test1	0.72
Yield Strength test 2	54.6ksi
Tensile Strength test 2	76.4ksi
Elongation test 2	29%
Elongation Gage Lgth test 2	8IN
Yield to tensile ratio test2	0.71

The Following is true of the material represented by this MTR:

- *Material is fully killed and is Hot Rolled Steel
- *100% melted, rolled, and manufactured in the USA
- *EN10204:2004 3.1 compliant
- *Contains no weld repair
- *Contains no Mercury contamination
- *Manufactured in accordance with the latest version of the plant quality manual
- *Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661
- *Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W