



CMC STEEL TEXAS  
1 STEEL MILL DRIVE  
SEGUIN TX 78155-7510

**CERTIFIED MILL TEST REPORT**  
For additional copies call  
830-372-8771

We hereby certify that the test results presented here  
are accurate and conform to the reported grade specification

Rolando A Davila

Quality Assurance Manager

**1SERIES-BPS<sup>®</sup>**

HEAT NO.:3116500 SECTION: SQUARE 1 x 20'0" A36/52950 GRADE: ASTM A36-19/A529-14 Gr50 ROLL DATE: 07/08/2022 MELT DATE: 06/30/2022 Cert. No.: 85090492 / 116500A862	S O L D T O	Superior Supply & Steel Co  318 N Cities Service Hwy Sulphur LA US 70663-5424 3376252300 3376258509	S H I P T O	Superior Supply & Steel  318 City Service Highway Sulphur LA US 70663-0000 3376252300 3376258509	Delivery#: 85090492 BOL#: 74861845 CUST PO#: 233866-11 CUST P/N: DLVRY LBS / HEAT: 4760.000 LB DLVRY PCS / HEAT: 70 EA
--	----------------------------	---	----------------------------	--	---

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.11%	Elongation test 2	30%		
Mn	1.12%	Elongation Gage Lgth test 2	8IN		
P	0.011%				
S	0.034%				
Si	0.19%				
Cu	0.24%				
Cr	0.07%				
Ni	0.08%				
Mo	0.020%				
V	0.000%				
Cb	0.017%				
Sn	0.009%				
Al	0.001%				
Carbon Eq A529	0.37%				
Yield Strength test 1	55.8ksi				
Tensile Strength test 1	74.3ksi				
Elongation test 1	29%				
Elongation Gage Lgth test 1	8IN				
Yield Strength test 2	55.3ksi				
Tensile Strength test 2	73.9ksi				
				<p><b>The Following is true of the material represented by this MTR:</b></p> <p>*Material is fully killed and is Hot Rolled Steel</p> <p>*100% melted and rolled in the USA</p> <p>*EN10204:2004 3.1 compliant</p> <p>*Contains no weld repair</p> <p>*Contains no Mercury contamination</p> <p>*Manufactured in accordance with the latest version of the plant quality manual</p> <p>*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661</p> <p>*Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a></p>	

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W