



CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT
For additional copies call
800-227-6489

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Rolando A Davila

Quality Assurance Manager

1SERIES-BPS[®]

HEAT NO.:3121049 SECTION: ANG 2 X 2x3/8 20"0" A36/52950 GRADE: ASTM A36-19/A529-14 Gr 50 ROLL DATE: 03/24/2023 MELT DATE: 03/05/2023 Cert. No.: 85378128 / 121049A713		Delivery#: 85378128 BOL#: 75290703 CUST PO#: P0240442 CUST P/N: DLVRY LBS / HEAT: 4700.000 LB DLVRY PCS / HEAT: 50 EA
--	--	--

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.10%	Elongation test 2	28%		
Mn	0.95%	Elongation Gage Lgth test 2	8IN		
P	0.012%				
S	0.038%				
Si	0.21%				
Cu	0.31%				
Cr	0.11%				
Ni	0.13%				
Mo	0.045%				
V	0.000%				
Cb	0.013%				
Sn	0.010%				
Al	0.000%				
Yield Strength test 1	53.0ksi				
Tensile Strength test 1	76.6ksi				
Elongation test 1	28%				
Elongation Gage Lgth test 1	8IN				
Yield Strength test 2	53.0ksi				
Tensile Strength test 2	76.6ksi				

The Following is true of the material represented by this MTR:

**Material is fully killed and is Hot Rolled Steel*

**100% melted, rolled, and manufactured in the USA*

**EN10204:2004 3.1 compliant*

**Contains no weld repair*

**Contains no Mercury contamination*

**Manufactured in accordance with the latest version of the plant quality manual*

**Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661*

**Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov*

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W