



CMC STEEL TEXAS  
1 STEEL MILL DRIVE  
SEGUN TX 78155-7510

CERTIFIED MILL TEST REPORT  
For additional copies call  
800-227-6489

We hereby certify that the test results presented here  
are accurate and conform to the reported grade specification

Quality Assurance Manager

*Rolando A Davila*  
Rolando A Davila

1SERIES-BPS<sup>®</sup>

HEAT NO.:3118961 SECTION: ANG 2 1/2 X 2 1/2x1/4 20'0" A36/52950 GRADE: ASTM A36-19/A529-14 Gr 50 ROLL DATE: 10/27/2022 MELT DATE: 10/08/2022 Cert. No.: 85310045 / 118961A397	S O	Superior Supply & Steel Co 318 N CITIES SERVICE HWY SULPHUR LA US 70663-5424	S H	Superior Supply & Steel Co 318 N CITIES SERVICE HWY SULPHUR LA US 70663-5424	Delivery#: 85310045 BOL#: 75193665 CUST PO#: P0239143-06 CUST P/N: DLVRY LBS / HEAT: 9348,000 LB DLVRY PCS / HEAT: 114 EA
	D T		P T		
	O	3376258509	O	3376258509	

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.10%	Yield to tensile ratio test1	0.74		
Mn	1.05%	Yield Strength test 2	57.3ksi		
P	0.016%	Tensile Strength test 2	77.2ksi		
S	0.033%	Elongation test 2	28%		
Si	0.21%	Elongation Gage Lgth test 2	8IN		
Cu	0.35%	Yield to tensile ratio test2	0.74		
Cr	0.13%				
Ni	0.12%				
Mo	0.036%				
V	0.000%				
Cb	0.013%				
Sn	0.011%				
Al	0.001%				
Carbon Eq A529	0.38%				
Carbon Eq A992	0.34%				
Yield Strength test 1	57.5ksi				
Tensile Strength test 1	77.2ksi				
Elongation test 1	32%				
Elongation Gage Lgth test 1	8IN				

The following is true of the material represented by this MTR:  
 \*Material is fully killed and is Hot Rolled Steel  
 \*100% melted, rolled, and manufactured in the USA  
 \*EN10204:2004 3.1 compliant  
 \*Contains no weld repair  
 \*Contains no Mercury contamination  
 \*Manufactured in accordance with the latest version of the plant quality manual  
 \*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661  
 \*Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

REMARKS : ALSO MEETS ASTM GRADE A36, A529, 50, A572-50, A709-35, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W