



CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT
For additional copies call
800-227-6489

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Drew M Fischer
Drew M Fischer
Quality Assurance Manager

1SERIES-BPS

HEAT NO.: 3121285
SECTION: FLAT 1/4x2 20'0" A36/52950
GRADE: ASTM A36-19/A529-19 GR 50
ROLL DATE: 03/24/2023
MELT DATE: 03/17/2023
Cert. No.: 85458373 / 121285A027

Superior Supply & Steel Co
318 N CITIES SERVICE HWY
SULPHUR LA
US 70663-5424
3376252300
3376258509

Superior Supply & Steel Co
318 N CITIES SERVICE HWY
SULPHUR LA
US 70663-5424
3376252300
3376258509

Delivery#: 85458373
BOL#: 75420133
CUST PO#: P0242330-01
CUST P/N:
DLVRY LBS / HEAT: 4692.000 LB
DLVRY PCS / HEAT: 138 EA

Characteristic Value

Characteristic Value

Characteristic Value

C 0.10%
Mn 1.06%
P 0.007%
S 0.032%
Si 0.24%
Cu 0.29%
Cr 0.06%
Ni 0.09%
Mo 0.028%
V 0.000%
Cb 0.011%
Sn 0.008%
Al 0.000%
Carbon Eq F1554 0.29%
Carbon Eq A529 0.36%

Yield Strength test 2 56.1ksi
Tensile Strength test 2 75.3ksi
Elongation test 2 27%
Elongation Gage Lgth test 2 8IN

Yield Strength test 2 56.1ksi
Tensile Strength test 2 75.3ksi
Elongation test 2 27%
Elongation Gage Lgth test 2 8IN

Yield Strength test 1 54.7ksi
Tensile Strength test 1 76.3ksi
Elongation test 1 27%
Elongation Gage Lgth test 1 8IN

The Following is true of the material represented by this MTR:
*Material is fully killed and is Hot Rolled Steel
*100% melted, rolled, and manufactured in the USA
*EN10204:2004 3.1 compliant
*Contains no weld repair
*Contains no Mercury contamination
*Manufactured in accordance with the latest version of the plant quality manual
*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661
*Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W