



CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT
For additional copies call
800-227-6489

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

1 SERIES-BPS

Quality Assurance Manager

Drew M Fischer

HEAT NO.: 3121024
SECTION: ANG 2 X 2X3/16 20"0"
A36/52950
GRADE: ASTM A36-19/A529-14 Gr 50
ROLL DATE: 05/26/2023
MELT DATE: 03/04/2023
Cert. No.: 85453464 / 121024A111

S Superior Supply & Steel Co
O 318 N CITIES SERVICE HWY
L SULPHUR LA
D US 70663-5424
T 3376252300
O 3376258509

S Superior Supply & Steel Co
H 318 N CITIES SERVICE HWY
I SULPHUR LA
P US 70663-5424
T 3376252300
O 3376258509

Delivery#: 85453464
BOL#: 75412982
CUST PO#: P0242044-01
CUST P/N:
DLVRY LBS / HEAT: 4685,000 LB
DLVRY PCS / HEAT: 96 EA

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.10%	Tensile Strength test 2	77.5ksi		
Mn	1.04%	Elongation test 2	27%		
P	0.009%	Elongation Gage Lgth test 2	8IN		
S	0.033%				
Si	0.22%				
Cu	0.30%				
Cr	0.08%				
Ni	0.11%				
Mo	0.042%				
V	0.000%				
Cb	0.012%				
Sn	0.009%				
Al	0.000%				
Carbon Eq A529	0.36%				
Yield Strength test 1	54.8ksi				
Tensile Strength test 1	76.9ksi				
Elongation test 1	30%				
Elongation Gage Lgth test 1	8IN				
Yield Strength test 2	54.5ksi				

The Following is true of the material represented by this MTR:
 * Material is fully killed and is Hot Rolled Steel
 * 100% melted, rolled, and manufactured in the USA
 * EN10204:2004 3.1 compliant
 * Contains no weld repair
 * Contains no Mercury contamination
 * Manufactured in accordance with the latest version of the plant quality manual
 * Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661
 * Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W