




CMC STEEL SOUTH CAROLINA  
 310 New State Road  
 Cayce SC 29033-3704

CERTIFIED MILL TEST REPORT  
 For additional copies call  
 800-227-6489

We hereby certify that the test results presented here  
 are accurate and conform to the reported grade specification

  
 Jacob Selzer – CMC Steel  
 Quality Assurance Manager

HEAT NO.:2110895 SECTION: ROUND 1/2 x 20'0" A36/52950 GRADE: ASTM A36-19/A529-19 Gr 50 ROLL DATE: 05/26/2024 MELT DATE: 05/24/2024 Cert. No.: 86014752 / 110895D027	S O L D T O	Superior Supply & Steel Co  318 N CITIES SERVICE HWY SULPHUR LA US 70663-5424 3376252300 3376258509	S H I P T O	Superior Supply & Steel Co  318 N CITIES SERVICE HWY SULPHUR LA US 70663-5424 3376252300 3376258509	Delivery#: 86014752 BOL#: 76249574 CUST PO#: P0252590-01 CUST P/N: DLVRY LBS / HEAT: 5050.000 LB DLVRY PCS / HEAT: 378 EA
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------	-----------------------------------------------------------------------------------------------------------------------	----------------------------	-----------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.14%	Elongation test 1	24%	<p>The Following is true of the material represented by this MTR:</p> <p><i>*Material is fully killed and is Hot Rolled Steel</i></p> <p><i>*100% melted, rolled, and manufactured in the USA</i></p> <p><i>*EN10204:2004 3.1 compliant *Contains no weld repair</i></p> <p><i>*Contains no Mercury contamination</i></p> <p><i>*Manufactured in accordance with the latest version of the plant quality manual</i></p> <p><i>*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661</i></p> <p><i>*Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a></i></p> <p><b>*THE RECORDING OF FALSE, FICTITIOUS OR FRAUDULENT STATEMENTS OR ENTRIES ON THIS DOCUMENT MAY BE PUNISHABLE AS A FELONY UNDER FEDERAL STATUTE</b></p>	
Mn	0.67%	Elongation Gage Lgth test 1	8IN		
P	0.010%	Reduction of Area test 1	52%		
S	0.025%	Yield to tensile ratio test1	0.77		
Si	0.20%	Yield Strength test 2	55.1ksi		
Cu	0.31%	Tensile Strength test 2	72.1ksi		
Cr	0.14%	Elongation test 2	23%		
Ni	0.12%	Elongation Gage Lgth test 2	8IN		
Mo	0.034%	Reduction of Area test 2	40%		
V	0.000%	Yield to tensile ratio test2	0.76		
Cb	0.010%	C+(Mn/6)	0.25%		
Sn	0.011%				
Al	0.001%				
B	0.0002%				
Ti	0.000%				
N	0.0173%				
Carbon Eq A529	0.35%				
Yield Strength test 1	55.6ksi				
Tensile Strength test 1	72.2ksi				

REMARKS :