CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT

For additional copies call
800-227-6489

We hereby certify that the test results presented here are accurate and conform to the reported grade specification

Drew M Fischer
Quality Assurance Manager

1SERIES-BPS ®

HEAT NO.:3137304 SECTION: FLAT 1/4x4 20'0" A36/52950 GRADE: ASTM A36-19/A529-19 GR 50 ROLL DATE: 02/26/2025 MELT DATE: 02/22/2025 Cert. No.: 86407386 / 137304A934	SOLD TO	Superior Supply & Steel Co 318 N CITIES SERVICE HWY SULPHUR LA US 70663-5424 3376252300 3376258509	SHIP TO	Superior Supply & Steel Co 318 N CITIES SERVICE HWY SULPHUR LA US 70663-5424 3376252300 3376258509	Delivery#: 86407386 BOL#: 76700542 CUST PO#: P0259187-01 CUST P/N: DLVRY LBS / HEAT: 8976.000 LB DLVRY PCS / HEAT: 132 EA

Characteristic	Value
C	0.10%
Mn	0.91%
P	0.010%
S	0.035%
Si	0.18%
Cu	0.34%
Cr	0.09%
Ni	0.12%
Mo	0.039%
V	0.000%
Cb	0.015%
Sn	0.010%
Al	0.001%
Carbon Eq F1554	0.27%
Carbon Eq A529	0.34%
Yield Strength test 1	58.0ksi
Tensile Strength test 1	75.8ksi
Elongation test 1	27%
Elongation Gage Lgth test 1	8IN

Characteristic	Value
Yield Strength test 2	59.0ksi
Tensile Strength test 2	76.5ksi
Elongation test 2	30%
Elongation Gage Lgth test 2	8IN

The Following is true of the material represented by this MTR:

**Material is fully killed and is Hot Rolled Steel*
**100% melted, rolled, and manufactured in the USA*
**EN10204:2004 3.1 compliant *Contains no weld repair*
**Contains no Mercury contamination*
**Manufactured in accordance with the latest version of the plant quality manual*
**Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661*
**Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov*
**THE RECORDING OF FALSE, FICTITIOUS OR FRAUDULENT STATEMENTS OR ENTRIES ON THIS DOCUMENT MAY BE PUNISHABLE AS A FELONY UNDER FEDERAL STATUTE*

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W
ALSO MEETS THE REQUIREMENTS OF ASME SA36