

## CMC STEEL SOUTH CAROLINA 310 New State Road Cayce SC 29033-3704

## CERTIFIED MILL TEST REPORT For additional copies call 830-372-8771

S

Н

Ρ

Т

0

## We hereby certify that the test results presented here are accurate and conform to the reported grade specification



Curtis G. Glenn.

**Quality Assurance Manager** 

HEAT NO.:2094622

SECTION: ROUND 1/2 x 20'0" A36/52950 GRADE: ASTM A36-19/A529-14 Gr 50

ROLL DATE: 03/14/2022 MELT DATE: 03/11/2022

Cert. No.: 85077052 / 094622D027

S O L D

0

Delivery#: 85077052 BOL#: 74839588 CUST PO#: 4500529033

CUST P/N: 901620 DLVRY LBS / HEAT: 10100.000 LB

DLVRY PCS / HEAT: 756 EA

Characteristic	Value	Characteristic	Value	Characteristic Value
С	0.13%	Elongation Gage Lgth test 1	8IN	
Mn	0.66%	Reduction of Area test 1	49%	
Р	0.009%	Yield to tensile ratio test1	0.77	
S	0.020%	Yield Strength test 2	53.8ksi	
Si	0.19%	Tensile Strength test 2	72.5ksi	
Cu	0.39%	Elongation test 2	26%	
Cr	0.13%	Elongation Gage Lgth test 2	8IN	
Ni	0.14%	Reduction of Area test 2	58%	
Мо	0.034%	Yield to tensile ratio test2	0.74	The Following is true of the material represented by this MTR:
V	0.000%	C+(Mn/6)	0.24%	*Material is fully killed and is Hot Rolled Steel
Cb	0.011%			*100% melted and rolled in the USA
Sn	0.015%			*EN10204:2004 3.1 compliant
Al	0.001%			*Contains no weld repair
В	0.0001%			*Contains no Mercury contamination
Ti	0.000%			*Manufactured in accordance with the latest version
N	0.0122%			of the plant quality manual
Carbon Eq A529	0.34%			*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661
Yield Strength test 1	55.9ksi			*Warning: This product can expose you to chemicals which are
Tensile Strength test 1	72.8ksi			known to the State of California to cause cancer, birth defects
Elongation test 1	26%			or other reproductive harm. For more information go
				to www.P65Warnings.ca.gov

REMARKS: