



CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT
For additional copies call
800-227-6489

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Rolando A Davila

Quality Assurance Manager

1SERIES-BPS®

HEAT NO.:3116795 SECTION: FLAT 1/4x4 20'0" A36/52950 GRADE: ASTM A36-19/A529-19 GR 50 ROLL DATE: 07/18/2022 MELT DATE: 07/14/2022 Cert. No.: 85098583 / 116795A934	S O L D T O	Superior Supply & Steel Co 318 N Cities Service Hwy Sulphur LA US 70663-5424 3376252300 3376258509	S H I P T O	Superior Supply & Steel 318 City Service Highway Sulphur LA US 70663-0000 3376252300 3376258509	Delivery#: 85098583 BOL#: 74873756 CUST PO#: 234701-11 CUST P/N: DLVRY LBS / HEAT: 8976.000 LB DLVRY PCS / HEAT: 132 EA
---	----------------------------	---	----------------------------	--	--

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.10%	Tensile Strength test 2	77.0ksi		
Mn	0.99%	Elongation test 2	27%		
P	0.022%	Elongation Gage Lgth test 2	8IN		
S	0.045%				
Si	0.21%				
Cu	0.29%				
Cr	0.13%				
Ni	0.14%				
Mo	0.037%				
V	0.000%				
Cb	0.016%				
Sn	0.010%				
Al	0.001%				
Carbon Eq F1554	0.29%				
Carbon Eq A529	0.37%				
Yield Strength test 1	57.7ksi				
Tensile Strength test 1	76.6ksi				
Elongation test 1	30%				
Elongation Gage Lgth test 1	8IN				
Yield Strength test 2	57.7ksi				

The Following is true of the material represented by this MTR:

- *Material is fully killed and is Hot Rolled Steel
- *100% melted and rolled in the USA
- *EN10204:2004 3.1 compliant
- *Contains no weld repair
- *Contains no Mercury contamination
- *Manufactured in accordance with the latest version of the plant quality manual
- *Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661
- *Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W