

CMC STEEL TEXAS

1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

0

CERTIFIED MILL TEST REPORT

For additional copies call 800-227-6489

We hereby certify that the test results presented here are accurate and conform to the reported grade specification

Douila Rolando A Davila

Quality Assurance Manager

1SERIES-BPS ®

HEAT NO.:3116799

SECTION: FLAT 1/4x4 20'0" A36/52950 GRADE: ASTM A36-19/A529-19 GR 50

ROLL DATE: 07/17/2022 MELT DATE: 07/14/2022

Cert. No.: 85123319 / 116799A934

S Superior Supply & Steel Co
O
L 318 N Cities Service Hwy
D Sulphur LA
US 70663-5424
T 3376252300

3376258509

S | Superior Supply & Steel H | I | 318 City Service Highway P | Sulphur LA | US | 70663-0000 T | 3376252300

3376258509

Delivery#: 85123319 BOL#: 74912520 CUST PO#: 235187-11 CUST P/N:

DLVRY LBS / HEAT: 4488.000 LB DLVRY PCS / HEAT: 66 EA

Characteristic	Value	Characteristic	Value	Characteristic Value
С	0.10%	Tensile Strength test 2	76.8ksi	
Mn	1.09%	Elongation test 2	28%	
P	0.012%	Elongation Gage Lgth test 2	8IN	
S	0.035%			
Si	0.21%			
Cu	0.30%			
Cr	0.10%			
Ni	0.10%			
Мо	0.029%			The Following is true of the material represented by this MTR:
V	0.000%			*Material is fully killed and is Hot Rolled Steel
Cb	0.016%			*100% melted, rolled, and manufactured in the USA
Sn	0.009%			*EN10204:2004 3.1 compliant
Al	0.001%			*Contains no weld repair
Carbon Eq F1554	0.30%			*Contains no Mercury contamination
Carbon Eq A529	0.37%			*Manufactured in accordance with the latest version
Yield Strength test 1	56.9ksi			of the plant quality manual
Tensile Strength test 1	76.5ksi			*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661
Elongation test 1	30%			*Warning: This product can expose you to chemicals which are
Elongation Gage Lgth test 1	8IN			known to the State of California to cause cancer, birth defects
Yield Strength test 2	56.4ksi			or other reproductive harm. For more information go
				to www.P65Warnings.ca.gov

0

REMARKS: ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W