



CMC STEEL TEXAS  
1 STEEL MILL DRIVE  
SEGUIN TX 78155-7510

**CERTIFIED MILL TEST REPORT**  
For additional copies call  
800-227-6489

We hereby certify that the test results presented here  
are accurate and conform to the reported grade specification

Rolando A Davila

Quality Assurance Manager

HEAT NO.:3115038 SECTION: ANG 1 1/2 X 1 1/2x3/16 20"0" A36/52950 GRADE: ASTM A36-19A529-14 GR 50 ROLL DATE: 06/29/2022 MELT DATE: 05/05/2022 Cert. No.: 85180719 / 115038A117	S O L D T O	Superior Supply & Steel Co 318 N Cities Service Hwy Sulphur LA US 70663-5424 3376252300 3376258509	S H I P T O	Superior Supply & Steel 318 City Service Highway Sulphur LA US 70663-0000 3376252300 3376258509	Delivery#: 85180719 BOL#: 74997537 CUST PO#: 236408-11 CUST P/N: DLVRY LBS / HEAT: 4680.000 LB DLVRY PCS / HEAT: 130 EA
---	----------------------------	---	----------------------------	--	--

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.17%	Elongation test 2	29%		
Mn	0.70%	Elongation Gage Lgth test 2	8IN		
P	0.013%				
S	0.033%				
Si	0.22%				
Cu	0.44%				
Cr	0.12%				
Ni	0.26%				
Mo	0.037%				
V	0.000%				
Cb	0.001%				
Sn	0.012%				
Al	0.003%				
Carbon Eq A529	0.40%				
Yield Strength test 1	54.6ksi				
Tensile Strength test 1	77.7ksi				
Elongation test 1	27%				
Elongation Gage Lgth test 1	8IN				
Yield Strength test 2	60.2ksi				
Tensile Strength test 2	83.0ksi				
					<p><b>The Following is true of the material represented by this MTR:</b></p> <p>*Material is fully killed and is Hot Rolled Steel</p> <p>*100% melted, rolled, and manufactured in the USA</p> <p>*EN10204:2004 3.1 compliant</p> <p>*Contains no weld repair</p> <p>*Contains no Mercury contamination</p> <p>*Manufactured in accordance with the latest version of the plant quality manual</p> <p>*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661</p> <p>*Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a></p>

REMARKS :