



CMC STEEL TEXAS
 1 STEEL MILL DRIVE
 SEGUIN TX 78155-7510

1 SERIES-BPS[®]

CERTIFIED MILL TEST REPORT
 For additional copies call
 800-227-6489

We hereby certify that the test results presented here
 are accurate and conform to the reported grade specification

Quality Assurance Manager

Rolando A Davila

HEAT NO.: 1080985
 SECTION: ANG 4 X 4x1/2 20'0" A36/52950
 GRADE: ASTM A36-19/A529-14 Gr 50
 ROLL DATE: 09/30/2022
 MELT DATE: 07/03/2022
 Cert. No.: 85181133 / 080985A682

S Superior Supply & Steel Co
 O 318 N Cities Service Hwy
 L Sulphur LA
 D US 70663-5424
 T 3376252300
 O 3376258509

S Superior Steel
 H 217 Darnall Rd
 I New Iberia LA
 P US 70560-0781
 T 8002529017
 O

Delivery#: 85181133
 BOL#: 74998553
 CUST PO#: 236439-11
 CUST P/N:
 DLVRY LBS / HEAT: 5120.000 LB
 DLVRY PCS / HEAT: 20 EA

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.15%	Elongation test 1	24%		
Mn	0.71%	Elongation Gage Lgth test 1	8IN		
P	0.013%	Yield to tensile ratio test1	0.70		
S	0.015%	Yield Strength test 2	54.8ksi		
Si	0.18%	Tensile Strength test 2	77.8ksi		
Cu	0.34%	Elongation test 2	25%		
Cr	0.15%	Elongation Gage Lgth test 2	8IN		
Ni	0.11%	Yield to tensile ratio test2	0.70		
Mo	0.032%				
V	0.003%				
Cb	0.012%				
Sn	0.011%				
B	0.0003%				
Ti	0.001%				
N	0.0099%				
Carbon Eq A6	0.34%				
Carbon Eq A529	0.37%				
Yield Strength test 1	54.3ksi				
Tensile Strength test 1	77.3ksi				

The following is true of the material represented by this MTR:
 *Material is fully killed and is Hot Rolled Steel
 *100% melted, rolled, and manufactured in the USA
 *EN10204:2004 3.1 compliant
 *Contains no weld repair
 *Contains no Mercury contamination
 *Manufactured in accordance with the latest version of the plant quality manual
 *Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661
 *Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W