



CMC STEEL TEXAS  
1 STEEL MILL DRIVE  
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT  
For additional copies call  
800-227-6489

We hereby certify that the test results presented here  
are accurate and conform to the reported grade specification

1SERIES-BPS<sup>®</sup>

Quality Assurance Manager

*Rolando A Davila*  
Rolando A Davila

HEAT NO.:3120655	S	Superior Supply & Steel Co	S	Superior Supply & Steel Co	Delivery#: 85310017
SECTION: FLAT 1/4x4 20'0" A36/52950	O	318 N CITIES SERVICE HWY	H	318 N CITIES SERVICE HWY	BOL#: 75193665
GRADE: ASTM A36-19/A529-19 GR 50	L	SULPHUR LA	I	SULPHUR LA	CUST PO#: P0239142-01
ROLL DATE: 01/19/2023	D	US 70663-5424	P	US 70663-5424	CUST P/N:
MELT DATE: 12/30/2022	T	3376252300	T	3376252300	DLVRY LBS / HEAT: 8976,000 LB
Cert. No.: 85310017 / 120655A934	O	3376258509	O	3376258509	DLVRY PCS / HEAT: 132 EA

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.12%	Yield Strength test 2	56.5ksi	The following is true of the material represented by this MTR: *Material is fully killed and is Hot Rolled Steel *100% melted, rolled, and manufactured in the USA *EN10204:2004 3.1 compliant *Contains no weld repair *Contains no Mercury contamination *Manufactured in accordance with the latest version of the plant quality manual *Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661 *Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>	
Mn	0.99%	Tensile Strength test 2	78.6ksi		
P	0.011%	Elongation test 2	31%		
S	0.027%	Elongation Gage Lgth test 2	8IN		
Si	0.21%				
Cu	0.29%				
Cr	0.10%				
Ni	0.12%				
Mn	0.058%				
V	0.000%				
Carbon Eq F1554	0.31%				
Carbon Eq A529	0.38%				
Yield Strength test 1	56.4ksi				
Tensile Strength test 1	78.3ksi				
Elongation test 1	26%				
Elongation Gage Lgth test 1	8IN				

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W

