'UCDR'

Mill Certification

11/16/2023

MTR#:1532862-10 Lot #:110004925860 8812 HWY 79 W Jewett, TX 75846 US

903 626-4461 Fax: 903 626-6290

Sold To: SUPERIOR SUPPLY & STEEL

PO BOX 2388

SULPHUR, LA 70664 US

Ship To: SUPERIOR SUPPLY 318 CITIES SERVICE HWY

HWY-108

SULPHUR, LA 70663 US

Customer PO	P0245378-01	Color Cod #	1
Product Group	Hot Roll - Merchant Bar Quality	Sales Order #	11066460 - 4.1
Grade		Product #	3016936
	Nucor Multigrade	Lot #	110004925860
Size	0.375" x 10"	Heat #	1100049258
BOL #	BOL-1579378	Load #	1532862
Description	Hot Roll - Merchant Bar Quality UM Plate 3/8" x 10" Nucor Multigrade 20' 0" [240"] 2001-6000 lbs	Customer Part #	1332602
Production Date	07/26/2023	Qty Shipped LBS	5104
Product Country Of Origin	United States	Qty Shipped EA	20
Original Item Description		Original Item	

I hereby certify that the material described herein has been manufactured in accordance with the specific

Melt Country of Origin: United States					Actions and standards listed above and that it satisfies those requirements. Melting Date: 07/16/2023						
<u>C (%)</u> 0.14	<u>Mn (%)</u> 0.85	P (%) 0.015	S (%) 0.018	Si (%) 0.232	Ni (%)	<u>Cr (%)</u> 0.21	Mo (%)	Cu (%) 0.21	Ti (%) 0.001	V (%) 0.044	Nb (%) 0.003
<u>Sn (%)</u>										0.011	0.000
0.011											

ASTM A529 S78.2 CE (%): 0.39

Tensile testing

	Yield (PSI)	Tensile (PSI)	Elongation in
(1)	57700	72300	8" (%) 23.0
(2)	56800	72600	21.0

Comments:
NUCOR MULTIGRADE MEETS THE REQUIREMENTS OF: ASTM A36/A36M-14; A529/529M-05(2009) GR50(345); A572/572M-07 GR50(345); A709/709M-10 GR36(250) & GR50(345); CSA G40.21-04 GR44W(300W)& GR50W(350W); AASHTO M270/M270M-10 GR36(270) & GR50(345); ASME SA36/SA36M-07; MEETS REPORTING REQUIREMENTS OF EN10204 SEC 3.1

- 1. All manufacturing processes of the steel, including melting, casting & hot rolling, have been performed in U.S.A
- 2. Mercury not intentionally added at any point during manufacturing or testing of this material.
- 3. Welding or weld repair was not performed on this material.
- 4. This material conforms to the specifications described on this document and may not be reproduced, except in full, without written approval of Nucor
- 5. Results reported ASTM E45 (Inclusion content) and ASTM E381 (Macro-etch) are provided as interpretation of ASTM procedures.