



CMC STEEL TEXAS  
1 STEEL MILL DRIVE  
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT  
For additional copies call  
800-227-6489

We hereby certify that the test results presented here  
are accurate and conform to the reported grade specification

Drew M. Fletcher

1 SERIES-BPS

Quality Assurance Manager

HEAT NO.: 1087792  
SECTION: CHANNEL 4"x5.4# 20'0"  
A36/52950  
GRADE: ASTM A36-19/A529-19 Gr50  
ROLL DATE: 08/28/2023  
MELT DATE: 07/26/2023  
Cert. No.: 85640500 / 087792A627

S Superior Supply & Steel Co  
O 318 N CITIES SERVICE HWY  
L SULPHUR LA  
D US 70663-5424  
T 3376252300  
O 3376258509

S Superior Supply  
H 1948 Grand Caillou Rd  
I Houma LA  
P US 70363-7085  
T 9852740111  
O

Delivery#: 85640500  
BOL#: 75714287  
CUST PO#: P0245955-15  
CUST P/N:  
DLVRY LBS / HEAT: 5184,000 LB  
DLVRY PCS / HEAT: 48 EA

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.11%	Elongation test 1	23%	The following is true of the material represented by this MTR: *Material is fully killed and is Hot Rolled Steel *100% melted, rolled, and manufactured in the USA *EN10204:2004 3.1 compliant *Contains no weld repair *Contains no Mercury contamination *Manufactured in accordance with the latest version of the plant quality manual *Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661 *Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
Mn	0.61%	Elongation Gage Lgth test 1	81N		
P	0.015%	Yield to tensile ratio test1	0.77		
S	0.026%	Yield Strength test 2	54.8ksi		
Si	0.15%	Tensile Strength test 2	70.7ksi		
Cu	0.39%	Elongation test 2	24%		
Cr	0.18%	Elongation Gage Lgth test 2	81N		
Ni	0.13%	Yield to tensile ratio test2	0.78		
Mn	0.037%				
V	0.003%				
Cb	0.008%				
Sn	0.011%				
B	0.0003%				
TI	0.001%				
N	0.0091%				
Carbon Eq A6	0.29%				
Carbon Eq A529	0.32%				
Yield Strength test 1	53.9ksi				
Tensile Strength test 1	70.1ksi				

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W