

CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT

For additional copies call 800-227-6489

Н

We hereby certify that the test results presented here are accurate and conform to the reported grade specification

Stew Lische

Drew M Fischer

1SERIES-BPS®

HEAT NO.:3123531 SECTION: ANG 2 X 2x1/8 20'0" A36/52950

GRADE: ASTM A36-19/A529-19 Gr 50 ROLL DATE: 07/04/2023 MELT DATE: 06/22/2023

Cert. No.: 85580210 / 123531A509

S Superior Supply & Steel Co
O
L 318 N CITIES SERVICE HWY

D SULPHUR LA US 70663-5424 T 3376252300 O 3376258509 Superior Supply & Steel Co

318 N CITIES SERVICE HWY

US 70663-5424 3376252300

SULPHUR LA

T 3376252300 O 3376258509 Delivery#: 85580210

BOL#: 75618568 CUST PO#: P0244606-01

CUST P/N:

Quality Assurance Manager

DLVRY LBS / HEAT: 4422.000 LB

DLVRY PCS / HEAT: 134 EA

Characteristic	Value	Characteristic	Value	Characteristic Value
С	0.10%	Tensile Strength test 2	76.8ksi	
Mn	0.84%	Elongation test 2	29%	
P	0.010%	Elongation Gage Lgth test 2	8IN	
S	0.043%			
Si	0.17%			
Cu	0.35%			
Cr	0.08%			
Ni	0.11%			
Мо	0.032%			The Following is true of the material represented by this MTR:
V	0.000%			*Material is fully killed and is Hot Rolled Steel
Cb	0.012%			*100% melted, rolled, and manufactured in the USA
Sn	0.008%			*EN10204:2004 3.1 compliant
Al	0.002%			*Contains no weld repair
Carbon Eq A529	0.32%			*Contains no Mercury contamination
•				*Manufactured in accordance with the latest version
Yield Strength test 1	59.1ksi			of the plant quality manual
Tensile Strength test 1	75.9ksi			*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661
Elongation test 1	26%			*Warning: This product can expose you to chemicals which are
Elongation Gage Lgth test 1	8IN			known to the State of California to cause cancer, birth defects
Yield Strength test 2	59.8ksi			or other reproductive harm. For more information go
				to www.P65Warnings.ca.gov

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W