

**SEGUIN TX 78155-7510** 1 STEEL MILL DRIVE CMC STEEL TEXAS

## **CERTIFIED MILL TEST REPORT** For additional copies call 800-227-6489

are accurate and conform to the reported grade specification We hereby certify that the test results presented here

Drew M Fischer

Quality Assurance Manager

## 1SERIES-BPS®

0 3376258509	0 3376258509	
T 3376252300	Т 3376252300	Cert. No.: 85599400 / 124245A737
US 70663-5424	US 70663-5424	MELT DATE: 07/22/2023
P SULPHUR LA	D SULPHUR LA	
I 318 N CITIES SERVICE HWY	L 318 N CITIES SERVICE HWY	GRADE: ASTM A36-19/A529-19 GR 50
I	0	20'0" A36/52950
S   Superior Supply & Steel Co	S Superior Supply & Steel Co	HEAT NO.:3124245

						_			_	_												
Elongation test	rensile orenigni rescri	Tencile Strongth test	Violal Ottowark toot 1	Carbon ed waaz	Carbon Eg 1992	Carbon Eq A529	Carbon Eq F1554	Δ	Sn	Сь			30	Z.	Çr	Cu	Si	S	P	Mn	C	Characteristic
20 /8	30%	71 7ksi	E) aksi	3	0 31%	0.35%	0.29%	0.002%	0.009%	0.017%	0.010/0	0.015%	0 025%	0.10%	0.05%	0.27%	0.21%	0.030%	0.007%	0.97%	0.11%	Value
															Yield to tensile ratio test2 0.75	Elongation Gage Lgth test 2 8IN	Elongation test 2 30%	Tensile Strength test 2 70.9ksi	Yield Strength test 2 52.9ksi	Yield to tensile ratio test1 0.74	Elongation Gage Lgth test 1 8IN	Characteristic Value
 to www.P65Warnings.ca.gov	or other reproductive harm. For more information go	known to the State of California to cause cancer, birth defects	*Warning: This product can expose you to chemicals which are	*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661	of the plant quality manual	*Manufactured in accordance with the latest version	Contains no Mercury contamination	Contains no were repair	לי בי אונים בי ביינול ביינול לי	*EM30204.2004.2.1 compliant	*100% melted, rolled, and manufactured in the USA	*Material is fully killed and is Hot Rolled Steel	The Following is true of the material represented by this wirk:									Characteristic Value

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W