



CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT
For additional copies call
800-227-6489

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Draw M Fischer
Draw M Fischer
Quality Assurance Manager

1SERIES-BPS ®

HEAT NO.: 3128768
SECTION: ANG 2 X 2x1/4 20"0" A36/52950
GRADE: ASTM A36-19/A529-19 Gr 50
ROLL DATE: 03/12/2024
MELT DATE: 02/11/2024
Cert. No.: 85763243 / 128768A113

S	Superior Supply & Steel Co	S	Superior Supply & Steel Co	Delivery#: 85763243
O	318 N CITIES SERVICE HWY	H	318 N CITIES SERVICE HWY	BOL#: 75906636
L	SULPHUR LA	I	SULPHUR LA	CUST PO#: P0248059-01
D	US 70663-5424	P	US 70663-5424	CUST P/N:
T	3376252300	T	3376252300	DLVRY LBS / HEAT: 4657,000 LB
O	3376258509	O	3376258509	DLVRY PCS / HEAT: 73 EA

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.10%	Tensile Strength test 2	73.9ksi	<p>The Following is true of the material represented by this MTR:</p> <p>*Material is fully killed and is Hot Rolled Steel</p> <p>*100% melted, rolled, and manufactured in the USA</p> <p>*EN10204:2004 3.1 compliant</p> <p>*Contains no weld repair</p> <p>*Contains no Mercury contamination</p> <p>*Manufactured in accordance with the latest version of the plant quality manual</p> <p>*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661</p> <p>*Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov</p>	
Mn	0.94%	Elongation test 2	32%		
P	0.008%	Elongation Gage Lgth test 2	8IN		
S	0.036%				
Si	0.18%				
Cu	0.35%				
Cr	0.07%				
Ni	0.11%				
Mo	0.031%				
V	0.000%				
Cb	0.013%				
Sn	0.011%				
Al	0.000%				
Carbon Eq A529	0.34%				
Yield Strength test 1	55.5ksi				
Tensile Strength test 1	74.2ksi				
Elongation test 1	32%				
Elongation Gage Lgth test 1	8IN				
Yield Strength test 2	55.5ksi				

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W
ALSO MEETS THE REQUIREMENTS OF ASME SA36