CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT

For additional copies call
800-227-6489

We hereby certify that the test results presented here are accurate and conform to the reported grade specification

Drew M Fischer

Quality Assurance Manager

1SERIES-BPS ®

HEAT NO.:3130663 SECTION: ANG 2 X 2x3/8 20'0" A36/52950 GRADE: ASTM A36-19/A529-19 Gr 50 ROLL DATE: 05/11/2024 MELT DATE: 05/06/2024 Cert. No.: 85875906 / 130663A713	SOLD TO	Superior Supply & Steel Co 318 N CITIES SERVICE HWY SULPHUR LA US 70663-5424 3376252300 3376258509	SHIP TO	Superior Supply & Steel Co 318 N CITIES SERVICE HWY SULPHUR LA US 70663-5424 3376252300 3376258509	Delivery#: 85875906 BOL#: 76066598 CUST PO#: P0250351-01 CUST P/N: DLVRY LBS / HEAT: 4700.000 LB DLVRY PCS / HEAT: 50 EA

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.11%	Tensile Strength test 2	74.3ksi		
Mn	0.84%	Elongation test 2	29%		
P	0.013%	Elongation Gage Lgth test 2	8IN		
S	0.035%				
Si	0.19%				
Cu	0.38%				
Cr	0.11%				
Ni	0.11%				
Mo	0.048%				
V	0.000%				
Cb	0.013%				
Sn	0.010%				
Al	0.002%				
Carbon Eq A529	0.35%				
Yield Strength test 1	53.9ksi				
Tensile Strength test 1	74.2ksi				
Elongation test 1	30%				
Elongation Gage Lgth test 1	8IN				
Yield Strength test 2	53.9ksi				

The Following is true of the material represented by this MTR:

**Material is fully killed and is Hot Rolled Steel*
**100% melted, rolled, and manufactured in the USA*
**EN10204:2004 3.1 compliant*
**Contains no weld repair*
**Contains no Mercury contamination*
**Manufactured in accordance with the latest version of the plant quality manual*
**Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661*
**Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov*

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W
ALSO MEETS THE REQUIREMENTS OF ASME SA36