

CMC STEEL TEXAS 1 STEEL MILL DRIVE SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT

For additional copies call 800-227-6489

We hereby certify that the test results presented here are accurate and conform to the reported grade specification

Stew Tische

Drew M Fischer

Quality Assurance Manager

HEAT NO.:3130178	S	Superior Supply & Steel Co	S	Superior Supply & Steel Co	Delivery#: 85960352
SECTION: ANG 1 1/2 X 1 1/2x1/4 20'0"	0		Н		BOL#: 76180515
A36/52950	L	318 N CITIES SERVICE HWY	ı	318 N CITIES SERVICE HWY	CUST PO#: 251802-01
GRADE: ASTM A36-19A529-19 GR 50	D	SULPHUR LA	Р	SULPHUR LA	CUST P/N:
ROLL DATE: 09/24/2024		US 70663-5424		US 70663-5424	DLVRY LBS / HEAT: 4586.000 LB
MELT DATE: 04/18/2024	Т	3376252300	Т	3376252300	DLVRY PCS / HEAT: 98 EA
Cert. No.: 85960352 / 130178A108	0	3376258509	0	3376258509	

Characteristic	Value	Characteristic	Value	Characteristic Value
С	0.12%	Tensile Strength test 2	75.1ksi	
Mn	1.00%	Elongation test 2	29%	
Р	0.011%	Elongation Gage Lgth test 2	8IN	
S	0.039%			
Si	0.16%			
Cu	0.32%			
Cr	0.08%			
Ni	0.09%			
Мо	0.032%			The Following is true of the material represented by this MTR:
V	0.028%			*Material is fully killed and is Hot Rolled Steel
Cb	0.001%			*100% melted, rolled, and manufactured in the USA
Sn	0.011%			*EN10204:2004 3.1 compliant *Contains no weld repair
Al	0.000%			*Contains no Mercury contamination
Carbon Eq A529	0.37%			*Manufactured in accordance with the latest version of the plant quality manual
				*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661
Yield Strength test 1	57.0ksi			*Warning: This product can expose you to chemicals which are
Tensile Strength test 1	75.1ksi			known to the State of California to cause cancer, birth defects or other
Elongation test 1	26%			reproductive harm. For more information go to www.P65Warnings.ca.gov
Elongation Gage Lgth test 1	8IN			*THE RECORDING OF FALSE, FICTITIOUS OR FRAUDULENT
Yield Strength test 2	56.8ksi			STATEMENTS OR ENTRIES ON THIS DOCUMENT MAY BE PUNISHABLE
				AS A FELONY UNDER FEDERAL STATUTE

REMARKS: