



CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT
For additional copies call
800-227-6489

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Drew M Fischer

1SERIES-BPS®

Quality Assurance Manager

HEAT NO.:1094190 SECTION: CHANNEL 8"x11.5# 20'0" A36/572T1 GRADE: ASTM A36-19/A572-21e1 Gr50 Tp1 ROLL DATE: 09/26/2024 MELT DATE: 07/19/2024 Cert. No.: 86014764 / 094190A827	S O L D T O	Superior Supply & Steel Co 318 N CITIES SERVICE HWY SULPHUR LA US 70663-5424 3376252300 3376258509	S H I P T O	Superior Supply & Steel Co 318 N CITIES SERVICE HWY SULPHUR LA US 70663-5424 3376252300 3376258509	Delivery#: 86014764 BOL#: 76249574 CUST PO#: P0252657-01 CUST P/N: DLVRY LBS / HEAT: 11040.000 LB DLVRY PCS / HEAT: 48 EA
---	----------------------------	---	----------------------------	---	--

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.11%	Elongation Gage Lgth test 1	8IN	The Following is true of the material represented by this MTR: <i>*Material is fully killed and is Hot Rolled Steel</i> <i>*100% melted, rolled, and manufactured in the USA</i> <i>*EN10204:2004 3.1 compliant *Contains no weld repair</i> <i>*Contains no Mercury contamination</i> <i>*Manufactured in accordance with the latest version of the plant quality manual</i> <i>*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661</i> <i>*Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov</i> <i>*THE RECORDING OF FALSE, FICTITIOUS OR FRAUDULENT STATEMENTS OR ENTRIES ON THIS DOCUMENT MAY BE PUNISHABLE AS A FELONY UNDER FEDERAL STATUTE</i>	
Mn	0.86%	Yield to tensile ratio test1	0.76		
P	0.011%	Yield Strength test 2	56.4ksi		
S	0.023%	Tensile Strength test 2	73.9ksi		
Si	0.18%	Elongation test 2	27%		
Cu	0.38%	Elongation Gage Lgth test 2	8IN		
Cr	0.10%	Yield to tensile ratio test2	0.76		
Ni	0.17%				
Mo	0.052%				
V	0.004%				
Cb	0.009%				
Sn	0.017%				
B	0.0003%				
Ti	0.001%				
N	0.0069%				
Carbon Eq A6	0.32%				
Yield Strength test 1	56.1ksi				
Tensile Strength test 1	73.7ksi				
Elongation test 1	27%				

REMARKS :