



CMC STEEL TEXAS  
1 STEEL MILL DRIVE  
SEGUN TX 78155-7510

CERTIFIED MILL TEST REPORT  
For additional copies call  
800-227-6489

We hereby certify that the test results presented here  
are accurate and conform to the reported grade specification

*Steve Truda*  
Steve Truda  
Quality Assurance Manager

1SERIES-BPS®

Quality Assurance Manager

HEAT NO.: 3128770  
SECTION: ANG 2 X 2x3/8 20'0" A36/52950  
GRADE: ASTM A36-19/A529-19 Gr 50  
ROLL DATE: 02/29/2024  
MELT DATE: 02/11/2024  
Cert. No.: 85724357 / 128770A713

S	Superior Supply & Steel Co	S	Superior Supply & Steel Co	Delivery#: 85724357
O		H		BOL#: 75846194
L	318 N CITIES SERVICE HWY	I	318 N CITIES SERVICE HWY	CUST PO#: P0247504-01
D	SULPHUR LA	P	SULPHUR LA	CUST P/N:
	US 70663-5424	T	US 70663-5424	DLVRY LBS / HEAT: 4700,000 LB
T	3376252300	O	3376252300	DLVRY PCS / HEAT: 50 EA
O	3376258509			

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.12%	Tensile Strength test 2	76.4ksi	<p>The Following is true of the material represented by this MTR:</p> <p>*Material is fully killed and is Hot Rolled Steel</p> <p>*100% melted, rolled, and manufactured in the USA</p> <p>*EN10204:2004 3.1 compliant</p> <p>*Contains no weld repair</p> <p>*Contains no Mercury contamination</p> <p>*Manufactured in accordance with the latest version of the plant quality manual</p> <p>*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661</p> <p>*Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a></p>	
Mn	0.90%	Elongation test 2	30%		
P	0.007%	Elongation Gage Lgth test 2	8IN		
S	0.023%				
Si	0.19%				
Cu	0.39%				
Cr	0.07%				
Ni	0.10%				
Mo	0.027%				
V	0.000%				
Carbon Eq A529	0.36%				
Yield Strength test 1	54.6ksi				
Tensile Strength test 1	76.4ksi				
Elongation test 1	33%				
Elongation Gage Lgth test 1	8IN				
Yield Strength test 2	54.9ksi				

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W  
ALSO MEETS THE REQUIREMENTS OF ASME SA36