



CMC STEEL ALABAMA
101 S 50TH STREET
BIRMINGHAM AL 35212-3525

CERTIFIED MILL TEST REPORT

For additional copies call
800-637-3227

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Marcus W. McCluney - CMC Steel AL

Quality Assurance Manager

1SERIES-BPS®

HEAT NO.:1081649 SECTION: FLAT 1x4 20'0" A36/52950 GRADE: ASTM A36-19/A529-19 GR 50 ROLL DATE: 08/07/2022 MELT DATE: 08/05/2022 Cert. No.: 85188351 / 081649B007	S O L D T O	S H I P T O	Delivery#: 85188351 BOL#: 75009502 CUST PO#: 4500535787 CUST P/N: 1010040020 DLVRY LBS / HEAT: 4896.000 LB DLVRY PCS / HEAT: 18 EA
---	--------------------------------	--------------------------------	---

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.17%	Elongation Gage Lgth test 1	8IN	<p>The Following is true of the material represented by this MTR:</p> <p>*Material is fully killed and is Hot Rolled Steel</p> <p>*100% melted, rolled, and manufactured in the USA</p> <p>*EN10204:2004 3.1 compliant</p> <p>*Contains no weld repair</p> <p>*Contains no Mercury contamination</p> <p>*Manufactured in accordance with the latest version of the plant quality manual</p> <p>*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661</p> <p>*Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov</p>	
Mn	0.71%	Yield to tensile ratio test1	0.71		
P	0.015%	Yield Strength test 2	55.0ksi		
S	0.026%	Tensile Strength test 2	78.8ksi		
Si	0.17%	Elongation test 2	24%		
Cu	0.34%	Elongation Gage Lgth test 2	8IN		
Cr	0.16%	Yield to tensile ratio test2	0.70		
Ni	0.12%				
Mo	0.036%				
V	0.004%				
Cb	0.011%				
Sn	0.013%				
B	0.0003%				
Ti	0.001%				
N	0.0116%				
Carbon Eq A6	0.36%				
Carbon Eq A529	0.39%				
Yield Strength test 1	55.2ksi				
Tensile Strength test 1	78.1ksi				
Elongation test 1	25%				

REMARKS : ALSO MEETS ASTM GRADE A36 REV 08, A572-50, A709-36, A709-50, A992, AASHTO GRADE M270-36, M270-50, CSA G40.21-04 GRADE 44W, 50W, ASME SA-36 2008A ADDEND A.