

CHEMICA C (%)	COMPOSITION Mn (%)	P (%)	S (%)	Si (%)	Cu (%)	Ni (%)	Cr (%)	Mo(%)	V (%)	Nb (%)	N (%)	CEqvA6 (%)	Sn (%)
0.08	0.98	0.015	0.021	0.26	0.29	0.13	0.13	0.033	0.048	0.001	0.0113	0.31	0.009

MECHANICAL PROPERTIES Elong. (%) G/L (Inches) UTS (PSI) UTS (MPa) YS 0.2% (PSI) YS (MPa) 24.70 73100 55500 383 8.000 504 73400 506 55400 382 24.00 8.000

COMMENTS / NOTES

This grade meets the requirements for the following grades: ASTM Grades: A36; A529-50; A572-50; A709-36; A709-50

CSA Grades: 44W; 50W

AASHTO Grades: M270-36; M270-50

ASME Grades: SA36

The above figures are certified chemical and physical test records as contained in the permanent records of the company. We certify that these data are correct and in compliance with specified requirements. No weld repair was performed on this material. The material has not been in contact with mercury while in Gerdau possession. For all products other than billets or beam blanks, this material was produced (Electric Arc Furnace, Melted, Continuously Cast, Hot Rolled and, if applicable, Cold-Drawn) in the USA. For billets or beam blanks, this material was produced (Electric Arc Furnace, Melted and Continuously Cast) in the USA. CMTR complies with EN 10204 3.1.

BHASKAR YALAMANCHILI

OUALITY DIRECTOR

Phone: (409) 267-1071 Email: Bhaskar.Yalamanchili@gerdau.com

Mackey

zames YA

QUALITY ASSURANCE MGR.

Phone: (770) 387 5718 Email: yan.wang@gerdau.com