

YS 0.2% (PSI)

53500

53000

UTS (MPa)

498

499

MECHANICAL PROPERTIES Elong. (%) 26.50 27.80

This grade meets the requirements for the following grades: ASTM Grades: A36; A529-50; A572-50; A709-36; A709-50

G/L (Inches)

8.000

8.000

CSA Grades: 44W; 50W

COMMENTS / NOTES

AASHTO Grades: M270-36; M270-50

ASME Grades: SA36

The above figures are certified chemical and physical test records as contained in the permanent records of the company. We certify that these data are correct and in compliance with specified requirements. No weld repair was performed on this material. The material has not been in contact with mercury while in Gerdau possession. For all products other than billets or beam blanks, this material was produced (Electric Arc Furnace, Melted, Continuously Cast, Hot Rolled and, if applicable, Cold-Drawn) in the USA. For billets or beam blanks, this material was produced (Electric Arc Furnace, Melted and Continuously Cast) in the USA. CMTR complies with EN 10204 3.1.

BHASKAR YALAMANCHILI

OUALITY DIRECTOR

UTS (PSI)

72200

72400

Phone: (409) 267-1071 Email: Bhaskar.Yalamanchili@gerdau.com

Mackey

YAN V

YS (MPa)

369

365

QUALITY ASSURANCE MGR.

Phone: (770) 387 5718 Email: yan.wang@gerdau.com