

Y/T rati (%)

0.790

0.780

G/L (Inches)

8.000

8.000

G/L (mm)

200.0

200.0

Elong. (%)

24.60

23.90

UTS (MPa)

493

502

COMMENTS / NOTES

YS 0.2% (PSI)

56348

56580

UTS (PSI)

71474

72749

Gerdau's steel is 100% recyclable. Support the circular economy through our Metals Recycling Partnership. For details, visit www2.gerdau.com/metals-recycling, or contact metalsrecycling@gerdau.com.

YS (MPa)

389

390

The above figures are certified chemical and physical test records as contained in the permanent records of the company. We certify that these data are correct and in compliance with specified requirements. No weld repair was performed on this material. The material has not been in contact with mercury while in Gerdau possession. For all products other than billets or beam blanks, this material was produced (Electric Arc Furnace, Melted, Continuously Cast, Hot Rolled and, if applicable, Cold-Drawn) in the USA. For billets or beam blanks, this material was produced (Electric Arc Furnace, Melted and Continuously Cast) in the USA. CMTR complies with EN 10204 3.1.

BHASKAR YALAMANCHILI

QUALITY DIRECTOR

Wale A. LL WADE LUMPKINS
QUALITY ASSURANCE MGR.

Phone: 972-779-3118 Email: Wade.Lumpkins@gerdau.com

Phone: (409) 267-1071 Email: Bhaskar.Yalamanchili@gerdau.com

Mackey