



300 Alumax Drive
TEXARKANA, TEXAS 75501 USA

* CERTIFICATION *

05/09/23
HEAT 4P4363
Lot 4P4363-004
Coil 4P4363-004C

ORDER S2301106 /1

----- YOUR ORDER & DATE -----
PO# 0601769 05/09/23

----- ITEM DESCRIPTION -----
.125" X 48" 5052-H32 ALUM COIL PAPER INTERLEAVE Country of Mfg.: U.S.A.
Customer Part# 787

----- SPECIFICATIONS -----
ASTM B209-14, AMS 4016M, AMS QQ A250/8

----- MECHANICAL PROPERTIES -----

	RESULTS	Standard			RESULTS	Standard	
		Min	Max			Min	Max
Elongation(%)	11	9.0		Tensile Strength,KSI	34.8	31.0	38.0
				Yield Strength,KSI	26.0	23.0	

----- CHEMICAL COMPOSITION -----

	RESULTS	Standard			RESULTS	Standard	
		Min	Max			Min	Max
Silicon (Si)	0.160		0.250	Iron (Fe)	0.310		0.400
Copper (Cu)	0.060		0.100	Manganese (Mn)	0.060		0.100
Chromium (Cr)	0.200	0.150	0.350	Magnesium (Mg)	2.400	2.200	2.800
Zinc (Zn)	0.005		0.100	Others, Total	0.030		0.150
Aluminum (Al)	96.775	Remainder		Other, Each			0.050

Quality Representative

Donna Compton *Donna Compton*