

0.029

0.001

YS 0.2% (PSI)

52900

53400

0.017

0.0096

YS (MPa)

365

368

0.010

23.10

COMMENTS / NOTES

MECHANICAL PROPERTIES Elong. (%)

23.70

0.12

This grade meets the requirements for the following grades: ASTM Grades: A36; A529-50; A572-50; A709-36; A709-50

0.014

0.026

G/L (Inches)

8.000

8.000

Mackey

0.22

0.26

UTS (PSI)

75200

75400

0.12

0.16

UTS (MPa)

519

520

CSA Grades: 44W; 50W

AASHTO Grades: M270-36; M270-50

0.90

ASME Grades: SA36

The above figures are certified chemical and physical test records as contained in the permanent records of the company. We certify that these data are correct and in compliance with specified requirements. No weld repair was performed on this material. The material has not been in contact with mercury while in Gerdau possession. For all products other than billets or beam blanks, this material was produced (Electric Arc Furnace, Melted, Continuously Cast, Hot Rolled and, if applicable, Cold-Drawn) in the USA. For billets or beam blanks, this material was produced (Electric Arc Furnace, Melted and Continuously Cast) in the USA. CMTR complies with EN 10204 3.1.

BHASKAR YALAMANCHILI

OUALITY DIRECTOR

Phone: (409) 267-1071 Email: Bhaskar. Yalamanchili@gerdau.com

yanus YAN

QUALITY ASSURANCE MGR.

Phone: (770) 387 5718 Email: yan.wang@gerdau.com