

S O L D

T

NUCOR - YAMATO STEEL COMPANY

P.O. Box 1228; Blytheville AR 72316

S H I P

T

CERTIFIED MILL TEST REPORT

100% Melted and Manufactured in the U.S.A.

ASTM A6/A6M-22

All Shapes produced by Nucor-Yamato Steel are cast and rolled to a fully killed and fine grain practice

Date 2023-10-23 11:50 AM ASTM A992/A992M-22 A572/A572M GR50-21 ASTM A709/A709M-21 GR50 (345) ASTM A709/A709M-21 GR50S (345S) CSA G40.21-13 50WM (345WM)

	Item Description	QTY	Heat	Mechanical Properties							Chemical Properties															
				Yield to Tensile Ratio	Yield Strength	Tensile Strength	ELONG	Charpy Impact																		
Item								° F	Impact Energy Ft•Lbf		/ Loc	С	Mn	Р	S	Si	Cu	Ni	Cr	Мо	V	Cb	CE	Sn	Pcm	CI
					KSI	KSI	%																			
					MPA	MPA	%	°C	J																	
1	W24X104.0 40 ft 0 in W610X155 (12 m)	1	583940	0.80	58	72	27																			
				0.79	57	72 28					.08	1.02	.012	.020	.20	.30	.12	.10	.03	.00	.018	.31	.01	.17		
					397	495																				
					391	494																				

ELONGATION BASED ON 8.00 INCH GAUGE LENGTH

C+Si/30+Mn/20+Cu/20+Ni/60+Cr/20+Mo/15+V/10+5B(B=Approx .0005)

Corrosion Index 26.01(%Cu)+3.88(%Ni)+1.2(%Cr)+1.49(%Si)+17.28(%P)-7.29(%Cu)(%Ni)-9.10(%Ni)(%P)-33.39(%Cu)^2

ISO 9001-2015 certified (Registration # 0985-07).

Meets mechanical lab independence requirements of EN10204 type 3.1.

The Charpy machine striker geometry used by Nucor-Yamato Steel is the 8 mm (0.315")striker (K) per ASTM A370 Section 22.1.2 and ISO 148-1 Section 7.3.

Day Lennell

Gary Pennell

Chief Metallurgist

County of Mississippi

Sworn to and subscribed before me amanda Stockman

On 2023-10-23

State of Arkansas

My commission expires on 03 / 25 / 2024

AMANDA F STOCKMAN NOTARY PUBLIC - ARKANSAS MISSISSIPPI COUNTY My Commission Expires 03-25-2024 Commission No. 12397936

This material was produced in accordance with the Nucor-Yamato Steel Quality Manual.

CARBON EQUIVALENT CE =C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15

Mercury has not been used in the direct manufacturing of this material

Boron has not been intentionally added and will not exceed 0.0008%

I hereby certify that the contents of this report are accurate and correct. All test results and operations performed by this material manufacturer are in compliance with the requirements of the material specifications, and when designated by the purchaser, meet the applicable specifications.