

499

500

54781

54567

378

376

GEOMETRIC CHARACTERISTICS

25.00

25.00

R:R

27.36

COMMENTS / NOTES

This grade meets the requirements for the following grades: ASTM Grades: A36; A529-50; A572-50; A709-36; A709-50

8.000

8.000

CSA Grades: 44W; 50W

AASHTO Grades: M270-36; M270-50

ASME Grades: SA36

Gerdau's steel is 100% recyclable. Support the circular economy through our Metals Recycling Partnership. For details, visit www2.gerdau.com/metals-recycling, or contact metalsrecycling@gerdau.com.

The above figures are certified chemical and physical test records as contained in the permanent records of the company. We certify that these data are correct and in compliance with specified requirements. No weld repair was performed on this material. The material has not been in contact with mercury while in Gerdau possession. For all products other than billets or beam blanks, this material was produced (Electric Arc Furnace, Melted, Continuously Cast, Hot Rolled and, if applicable, Cold-Drawn) in the USA. For billets or beam blanks, this material was produced (Electric Arc Furnace, Melted and Continuously Cast) in the USA. CMTR complies with EN 10204 3.1.

BHASKAR YALAMANCHILI

OUALITY DIRECTOR

72357

72568

CHULL DANIEL K WELLS

QUALITY ASSURANCE MGR.

Phone: (563) 279-1238 Email: Daniel.wells1@gerdau.com

Phone: (409) 267-1071 Email: Bhaskar.Yalamanchili@gerdau.com

Mackey