

CMC STEEL ALABAMA 101 S 50TH STREET BIRMINGHAM AL 35212-3525

CERTIFIED MILL TEST REPORT For additional copies call 800-637-3227

We hereby certify that the test results presented here are accurate and conform to the reported grade specification

Marcus W. McCluney - CMC Steel AL

Quality Assurance Manager

1SERIES-BPS ®

HEAT NO.:1090118

SECTION: FLAT 1/4x7 20'0" A36/52955 GRADE: ASTM A36-19/A529-19 Gr 55

ROLL DATE: 12/06/2023 MELT DATE: 11/30/2023

Cert. No.: 85647148 / 090118B784

Delivery#: 85647148 BOL#: 75723972

CUST PO#: 4500564829 CUST P/N: 10870020

DLVRY LBS / HEAT: 4998.000 LB DLVRY PCS / HEAT: 42 EA

Characteristic	Value	Characteristic	Value	Characteristic Value
С	0.14%	Elongation test 1	25%	
Mn	0.63%	Elongation Gage Lgth test 1	8IN	
Р	0.008%	Yield to tensile ratio test1	0.74	
S	0.025%	Yield Strength test 2	57.1ksi	
Si	0.16%	Tensile Strength test 2	76.7ksi	
Cu	0.25%	Elongation test 2	25%	
Cr	0.13%	Elongation Gage Lgth test 2	8IN	
Ni	0.11%	Yield to tensile ratio test2	0.74	
· Mo	0.029%	>		The Following is true of the material represented by this MTR:
V	0.005%			*Material is fully killed and is Hot Rolled Steel
Cb	0.011%			*100% melted, rolled, and manufactured in the USA
Sn	0.008%			*EN10204:2004 3.1 compliant
В	0.0001%			*Contains no weld repair
Ti	0.001%			*Contains no Mercury contamination
N	0.0101%			*Manufactured in accordance with the latest version
Carbon Eq A6	0.31%			of the plant quality manual
Carbon Eq A529	0.34%			*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661
				*Warning: This product can expose you to chemicals which are
Yield Strength test 1	56.9ksi			known to the State of California to cause cancer, birth defects
Tensile Strength test 1	76.7ksi			or other reproductive harm. For more information go
				to www.P65Warnings.ca.gov

REMARKS: ALSO MEETS ASTM GRADE A36, A529-50, A529-55, A572-50, A572-55, A709-36, A709-50, AASHTO M270-36, M270-50, CSA G40.21-04 44W,50W, 55W ASME SA-36 2008A ADDEND A