NUCOR

## **Mill Certification**

02/06/2024

MTR#:1590232-4 Lot #:110005126520 8812 HWY 79 W Jewett, TX 75846 US 903 626-4461 Fax: 903 626-6290

Ship To: CPU RYDER

4750 W MARSHALL AVE LONGVIEW, TX 75604 US

Customer PO	4500568060	Sales Order #	11069179 - 2.1
Product Group	Hot Roll - Merchant Bar Quality	Product #	3005019
Grade	A36/A529 Gr 50, CSA 44W/50W	Lot #	110005126520
Size	1.25" x 1.25" x 0.1875"	Heat #	1100051265
BOL #	BOL-1636643	Load #	1590232
Description	Hot Roll - Merchant Bar Quality Equal Angle 1 1/4" x 1 1/4" x 3/16" A36/A529 Gr 50, CSA 44W/50W 20' 0" [240"] 2001-6000 lbs	Customer Part #	50108108620
Production Date	09/27/2023	Qty Shipped LBS	4884
Product Country Of Origin	United States	Qty Shipped EA	165
Original Item Description		Original Item Number	

I hereby certify that the material described herein has been manufactured in accordance with the specifications and standards listed above and that it satisfies those requirements.

Melt Country of Origin : United States							Melting Date: 09/14/2023					
	<u>C (%)</u>	<u>Mn (%)</u>	<u>P (%)</u>	<u>S (%)</u>	<u>Si (%)</u>	<u>Ni (%)</u>	<u>Cr (%)</u>	<u>Mo (%)</u>	<u>Cu (%)</u>	<u>V (%)</u>	<u>Nb (%)</u>	
	0.13	0.80	0.018	0.016	0.188	0.11	0.23	0.03	0.26	0.027	0.001	
Reduction Ratio 89.64 : 1 <u>Tensile testing</u> Yield (PSI) Tensile (PSI) Elongation in 8" (%)												
(1)		54000	70	70500								
(2)		55000	71	200	27.0							

## Comments:

MEETS THE REQUIREMENTS OF: ASTM A36/A36M-14; A529/A529-05 GR50(345); A572/572M-07 GR50(345); A709/A709M-10 GR36(250); CSA G40.21-04 GR44W(300W)&GR50W(350W); AASHTO M270/270M-10 GR36(270); ASME SA36/SA36M-10; MEETS REPORTING REQUIREMENTS OF EN10204 SEC 3.1

1. All manufacturing processes of the steel, including melting, casting & hot rolling, have been performed in U.S.A

2. Mercury not intentionally added at any point during manufacturing or testing of this material.

3. Welding or weld repair was not performed on this material.

4. This material conforms to the specifications described on this document and may not be reproduced, except in full, without written approval of Nucor Corporation.

5. Results reported ASTM E45 (Inclusion content) and ASTM E381 (Macro-etch) are provided as interpretation of ASTM procedures.

Man