CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT

For additional copies call
800-227-6489

We hereby certify that the test results presented here are accurate and conform to the reported grade specification

Drew M Fischer
Quality Assurance Manager

1SERIES-BPS ®

HEAT NO.:3133029 SECTION: ANG 2 X 2x3/8 20'0" A36/52950 GRADE: ASTM A36-19/A529-19 Gr 50 ROLL DATE: 08/19/2024 MELT DATE: 08/17/2024 Cert. No.: 86044704 / 133029A713	SOLD TO Superior Supply & Steel Co 318 N CITIES SERVICE HWY SULPHUR LA US 70663-5424 3376252300 3376258509	SHIP TO Superior Supply & Steel Co 318 N CITIES SERVICE HWY SULPHUR LA US 70663-5424 3376252300 3376258509	Delivery#: 86044704 BOL#: 76286879 CUST PO#: P0253213-01 CUST P/N: DLVRY LBS / HEAT: 4700.000 LB DLVRY PCS / HEAT: 50 EA

Characteristic	Value
C	0.09%
Mn	0.87%
P	0.010%
S	0.038%
Si	0.21%
Cu	0.33%
Cr	0.05%
Ni	0.11%
Mo	0.031%
V	0.000%
Cb	0.016%
Sn	0.010%
Al	0.003%
Carbon Eq A529	0.32%
Yield Strength test 1	55.0ksi
Tensile Strength test 1	72.5ksi
Elongation test 1	30%
Elongation Gage Lgth test 1	8IN
Yield Strength test 2	55.9ksi

Characteristic	Value
Tensile Strength test 2	72.8ksi
Elongation test 2	28%
Elongation Gage Lgth test 2	8IN

Characteristic	Value

The Following is true of the material represented by this MTR:

**Material is fully killed and is Hot Rolled Steel*
**100% melted, rolled, and manufactured in the USA*
**EN10204:2004 3.1 compliant *Contains no weld repair*
**Contains no Mercury contamination*
**Manufactured in accordance with the latest version of the plant quality manual*
**Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661*
**Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov*
**THE RECORDING OF FALSE, FICTITIOUS OR FRAUDULENT STATEMENTS OR ENTRIES ON THIS DOCUMENT MAY BE PUNISHABLE AS A FELONY UNDER FEDERAL STATUTE*

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W
ALSO MEETS THE REQUIREMENTS OF ASME SA36